NSN 5985-01-244-0563

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-244-0563

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Err-090
Terminal Material:
Steel, corrosion resisting
Terminal Surface Treatment:
Gold plated or passivated
Body Surface Treatment:
Gold plated or passivated
Overall Length:
1.020 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-28.0/+90.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
15.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Shelf Life:
N/a

NSN 5985-01-244-0563

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000