NSN 5985-01-244-0568

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-244-0568 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 2.620 inches **Overall Height:** 0.500 inches **Overall Width:** 1.880 inches **Shaft Length:** Between 0.690 inches and 0.810 inches **Distance Between Mounting Facility Centers:** 1.625 inches **Voltage Standing Wave Ratio:** 1.80 **Coaxial Connector Series Designation:** Sma **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Mounting Facility Type And Quantity:** 1 flange w/mounting hole Frequency Range: Between 2.000 gigahertz and 4.000 gigahertz **Adjustment Device Type And Quantity:** 1 shaft **Mounting Facility Pattern:** Two position in-line **Shaft Type:** Round, slotted **Terminal Type And Quantity:** 2 connector, coaxial, female **Specification Data:** 23991-47d530797+1 manufacturers source control **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-01-244-0568

Variable Attenuator - Page 2 of 2



Fiig:

A223a0