## NSN 5985-01-244-4083

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-244-4083

Ap	plicatio	on Des	ign:

Transmission line

**Body Material:** 

Steel, stainless

Body Style:

Err-090

#### **Body Surface Treatment:**

Any acceptable

**Overall Length:** 

1.020 inches

**Overall Diameter:** 

0.280 inches

**Operating Tempurature Range:** 

-65.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

## 1.15 and 1.20 and 1.25

Input Impedance Rating In Ohms:

50.0

**Output Impedance Rating In Ohms:** 

50.0

**Coaxial Connector Series Designation:** 

Sma

#### **Power Rating:**

2.0 watts average

## **Rf Signal Attenuation In Decibels:**

16.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

## Attenuation Accuracy Reference Frequency:

12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

#### **Mounting Method:**

Connector

## **Terminal Type And Quantity:**

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Shelf Life:

N/a

Unit Of Measure:

---

# NSN 5985-01-244-4083

Fixed Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A20000

