NSN 5985-01-245-5460

Waveguide Assembly - Page 1 of 2



85-01-245-5460

View Online at https://aerobasegroup.com/nsn/598
Unable To Decode:
Internal, rectangular external, rectangular
Thread Class:
2b all flanges all connection facilities
Thread Direction:
Right-hand all flanges all connection facilities
Unable To Decode:
Corrugated single tubing segment
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.10
Insertion Loss In Decibels:
0.01
Maximum Operating Pressure:
15.0 pounds per square inch gage
Flange Connecting Facility And Quantity:
8 threaded hole all flanges all connection facilities
Waveguide Length:
4.000 inches
Flexibility:
Flexible single tubing segment
Material:
Copper alloy single flange
Precious Material And Location:
surfaces gold
Precious Material:
Gold
Surface Treatment:
Gold all tubing segment and flange all surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc all flanges all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5985-01-245-5460 Waveguide Assembly - Page 2 of 2



Fiig:

A073a0