NSN 5985-01-246-0381

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-246-0381

Application Design:
Body Material:
Aluminum
Body Style:
Err-090
Body Surface Treatment:
Anodized
Overall Length:
Between 1.210 inches and 1.270 inches
Overall Diameter:
Between 0.615 inches and 0.635 inches
Operating Tempurature Range:
-0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
5.5 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+6.0 gigahertz and +6.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Frequency Sensitivity Attenuation In Decibels:
0.30
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz

NSN 5985-01-246-0381

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000