## NSN 5985-01-246-3216

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-246-3216

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange second connection facility

**Thread Direction:** 

Right-hand first flange second connection facility

Bend Angle In Deg:

90.0 third bend h-plane

**Tubing Wall Construction Style:** 

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

Flange Depth:

0.423 inches first flange and 0.453 inches first flange

**Voltage Standing Wave Ratio:** 

1.20

**Insertion Loss In Decibels:** 

0.40

**Waveguide Outside Width:** 

Between 0.996 inches and 1.004 inches

**Thread Size:** 

0.190 inches first flange second connection facility

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:** 

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:** 

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange second connection facility

Waveguide First Leg Length:

1.215 inches

## **NSN 5985-01-246-3216** Waveguide Assembly - Page 2 of 2



Waveguide Fifth Leg Length:
6.895 inches
Flange Style:
Choke type first flange
Waveguide Second Leg Length:
1.400 inches
Waveguide Third Leg Length:
4.370 inches
Waveguide Fourth Leg Length:
4.400 inches
Flexibility:
Rigid all tubing segment
Material:
Aluminum alloy 6061 all tubing segment and flange
Precious Material And Location:
External surfaces gold and external surfaces silver
Precious Material:
Gold and silver
Surface Treatment:
Silver all tubing segment outside surfaces and gold all tubing segment outside surfaces
Style Designator:
Four bend type
Thread Series Designator:
Unf first flange second connection facility
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A073a0