NSN 5985-01-246-6337

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-246-6337 **Application Design:** Transmission line **Body Material:** Aluminum alloy **Body Style:** Round, terminal/terminals on one surface **Terminal Material:** Any acceptable **Terminal Surface Treatment:** Any acceptable **Body Surface Treatment:** Any acceptable **Overall Height:** Between 0.740 inches and 0.760 inches **Overall Diameter:** Between 0.350 inches and 0.370 inches **Center To Center Distance Between Terminals:** 0.100 inches **Operating Tempurature Range:** -55.0/+71.0 degrees celsius **Voltage Standing Wave Ratio:** 1.35 **Input Impedance Rating In Ohms: Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 100.0 milliwatts average Rf Signal Attenuation In Decibels: 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+1.0 gigahertz **Attenuation Accuracy In Decibels:** -0.10/+0.10 **Unpackaged Unit Weight:** 0.003 pounds **Mounting Method: Terminal Terminal Type And Quantity:**

3 pin

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

NSN 5985-01-246-6337

Fixed Attenuator - Page 2 of 2



Fsc App	lication	Data:
---------	----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000