NSN 5985-01-247-7403

Waveguide Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-247-7403

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b single flange all connection facilities

Thread Direction:

Right-hand single flange all connection facilities

End Application:

Test set, radar an/apm-440

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

1

Flange Inside Width:

0.896 inches single flange and 0.904 inches single flange

Flange Inside Height:

0.396 inches single flange and 0.404 inches single flange

Flange Outside Width:

1.610 inches single flange and 1.640 inches single flange

Flange Outside Height:

1.610 inches single flange and 1.640 inches single flange

Flange Inside Diameter:

1.406 inches single flange and 1.437 inches single flange

Flange Depth:

0.423 inches single flange and 0.453 inches single flange

Voltage Standing Wave Ratio:

1.10

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Thread Length:

0.438 inches single flange all connection facilities

Adapter Length:

1.150 inches

Adapter Height:

Between 1.610 inches and 1.640 inches

Thready Qty Per Inch (tpi):

32 single flange all connection facilities

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches single flange all connection facilities

NSN 5985-01-247-7403

Waveguide Adapter - Page 2 of 2



Waveguide Inside Width:
Between 0.896 inches and 0.904 inches
Waveguide Inside Height:
Between 0.396 inches and 0.404 inches
Waveguide Outside Height:
Between 0.496 inches and 0.504 inches
Flange Connecting Facility And Quantity:
4 threaded hole single flange all connection facilities
Flange Style:
Choke type single flange
Adapterheight:
1.593 inches
Adapterwidth:
Between 1.610 inches and 1.640 inches
Material:
Aluminum alloy single tubing segment and flange
Surface Treatment:
Any acceptable single tubing segment and flange outside surfaces
Style Designator:
Waveguide to coaxial
Thread Series Designator:
Unc single flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0