## NSN 5985-01-250-4812

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-250-4812

Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Nickel plated
Overall Length:
1.700 inches
Overall Diameter:
0.430 inches
Voltage Standing Wave Ratio:
1.30 and 1.50 and 1.70
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+0.5 gigahertz and +0.5/+1.0 gigahertz and +1.0/+1.5 gigahertz
Attenuation Accuracy Reference Frequency:
1.5 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1.500 gigahertz
Fsc Application Data:
Shelf Life:
Antennas, waveguides and related equip.
Sneit Lite:

N/a

## NSN 5985-01-250-4812

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000