NSN 5985-01-250-5929

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-250-5929 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Terminal Material:** Steel, stainless **Terminal Surface Treatment:** Passivated **Body Surface Treatment: Passivated Overall Length:** 1.570 inches **Overall Diameter:** 0.650 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.07 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Tnc **Power Rating:** 2.0 watts average Rf Signal Attenuation In Decibels: 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+8.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Frequency Sensitivity Attenuation In Decibels: Temperature Sensitivity Attenuation In Decibels:** 0.00005

0.00005

Mounting Method:

Connector

Terminal Type And Quantity:
2 connector

NSN 5985-01-250-5929

Fixed Attenuator - Page 2 of 2



Frequency	Range	
-----------	-------	--

Between 0.000 hertz and 8.000 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000