NSN 5985-01-253-2606

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-253-2606

Application Design:
Transmission line
Body Material:
Aluminum alloy or steel
Body Style:
Coaxial type
Overall Length:
2.060 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches
Overall Height:
2.360 inches
Overall Width:
2.600 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Operating Tempurature Range:
-54.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Tnc
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.6
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 flange w/mounting hole
Frequency Range:
Between 0.000 hertz and 30.000 megahertz
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:

50.0 input-output

NSN 5985-01-253-2606

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity	/:
----------------------------	----

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0