NSN 5985-01-253-4235

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-253-4235

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Overall Length:
1.250 inches
Overall Height:
0.390 inches
Overall Width:
0.390 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
0.2 watts average
0.2 watts average Rf Signal Attenuation In Decibels:
•
Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels: 6.0
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function:
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity:
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range:
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life:
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a Unit Of Measure:
Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: