NSN 5985-01-253-4235

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-253-4235

| Application Design: |
|---|
| Transmission line |
| Body Material: |
| Steel, stainless |
| Body Style: |
| Rectangular, terminal/terminals on opposite surfaces |
| Overall Length: |
| 1.250 inches |
| Overall Height: |
| 0.390 inches |
| Overall Width: |
| 0.390 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.30 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| |
| 0.2 watts average |
| 0.2 watts average Rf Signal Attenuation In Decibels: |
| • |
| Rf Signal Attenuation In Decibels: |
| Rf Signal Attenuation In Decibels: 6.0 |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a Unit Of Measure: |
| Rf Signal Attenuation In Decibels: 6.0 Connection Type Per Function: Female input and male output Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a Unit Of Measure: Demilitarization: |