NSN 5985-01-254-2192



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-01-254-2192
Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Err-090
Terminal Material:
Beryllium copper, qq-c-530
Terminal Surface Treatment:
Gold plated, mil-g-45204
Body Surface Treatment:
Passivated, qq-p-35
Overall Length:
2.000 inches
Overall Diameter:
0.734 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
4.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy In Decibels:
0.50/.0.50

-0.50/+0.50

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Contact surfaces gold

NSN 5985-01-254-2192

Fixed Attenuator - Page 2 of 2



P	reci	nus	Material	ŀ

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000