## NSN 5985-01-254-2202

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-254-2202

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
5.060 inches
Overall Width:
2.150 inches
Voltage Standing Wave Ratio:
1.35 and 1.50
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 1.0 kilowatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0/+101.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
101
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1.500 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
8 pushbutton
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5985-01-254-2202

Variable Attenuator - Page 2 of 2



Fiig:

A223a0