## NSN 5985-01-256-6746

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-256-6746

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Terminal Material:
Beryllium copper
Terminal Surface Treatment:
Bright alloy
Body Surface Treatment:
Passivated
Overall Length:
1.250 inches
Overall Diameter:
0.312 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.35 and 1.60
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Wpm
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz and +18.0/+26.5 gigahertz
Attenuation Accuracy In Decibels:
-0.60/+0.60
Temperature Sensitivity Attenuation In Decibels:
0.0001
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:

Between 0.000 hertz and 26.500 gigahertz

## NSN 5985-01-256-6746

Fixed Attenuator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000