NSN 5985-01-258-0740

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Steel, corrosion resisting



View Online at https://aerobasegroup.com/nsn/5985-01-258-0740

Body Style:
Err-090
Terminal Material:
Steel, corrosion resisting
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Passivated
Overall Length:
1.875 inches
Overall Diameter:
0.547 inches
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
52.5
Output Impedance Rating In Ohms:
52.5
Coaxial Connector Series Designation:
Coaxial Connector Series Designation: Bnc
Bnc
Bnc Power Rating:
Power Rating: 0.5 watts average
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels:
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range:
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels:
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method:
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity:
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1000.000 megahertz
Power Rating: 0.5 watts average Rf Signal Attenuation In Decibels: 4.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1000.0 megahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 1000.000 megahertz Shelf Life:

NSN 5985-01-258-0740

Fixed Attenuator - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A20000