NSN 5985-01-260-2460

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-260-2460

Application Design:
Transmission line
Body Material:
Steel
Body Style:
Coaxial type
Overall Length:
2.440 inches
Overall Height:
1.610 inches
Overall Width:
1.300 inches
Scale Linearity:
Linear
Shaft Diameter:
0.250 inches
Shaft Length:
0.640 inches
Distance Between Mounting Facility Centers:
0.750 inches
Operating Tempurature Range:
-55.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+5.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
0.5
Mounting Facility Type And Quantity:

2 connector and 2 threaded hole

NSN 5985-01-260-2460

Variable Attenuator - Page 2 of 2



Frequency Range:
Between 1200.000 megahertz and 1400.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
3 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A223a0