

View Online at <https://aerobasegroup.com/nsn/5985-01-262-2554>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

End Application:

An/mst-t1a radar set

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.368 inches all flanges and 1.376 inches all flanges

Flange Inside Height:

0.618 inches all flanges and 0.626 inches all flanges

Flange Outside Diameter:

3.110 inches all flanges and 3.340 inches all flanges

Flange Depth:

0.735 inches all flanges and 0.765 inches all flanges

Voltage Standing Wave Ratio:

1.10

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

Thread Size:

0.190 inches all flanges all connection facilities

Waveguide Inside Width:

Between 1.368 inches and 1.376 inches

Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

Waveguide Outside Height:

Between 0.746 inches and 0.754 inches

Flange Connecting Facility And Quantity:

6 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Length:

Between 3.875 inches and 4.125 inches

Special Features:

T.O.-43-D71-924;

Flexibility:

Flexible single tubing segment

Material:

Rubber single tubing jacket

Precious Material And Location:

Internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver all tubing segment and flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0