# NSN 5985-01-262-2554

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-262-2554

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b all flanges all connection facilities

**Thread Direction:** 

Right-hand all flanges all connection facilities

**End Application:** 

An/mst-t1a radar set

## **Tubing Wall Construction Style:**

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

1.368 inches all flanges and 1.376 inches all flanges

# Flange Inside Height:

0.618 inches all flanges and 0.626 inches all flanges

#### Flange Outside Diameter:

3.110 inches all flanges and 3.340 inches all flanges

# Flange Depth:

0.735 inches all flanges and 0.765 inches all flanges

# **Voltage Standing Wave Ratio:**

1.10

#### **Maximum Operating Pressure:**

30.0 pounds per square inch gage

## **Waveguide Outside Width:**

Between 1.496 inches and 1.504 inches

# Thread Size:

0.190 inches all flanges all connection facilities

#### **Waveguide Inside Width:**

Between 1.368 inches and 1.376 inches

# Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

# **Waveguide Outside Height:**

Between 0.746 inches and 0.754 inches

# Flange Connecting Facility And Quantity:

6 threaded hole all flanges all connection facilities

# Flange Style:

Choke type all flanges

# Waveguide Length:

Between 3.875 inches and 4.125 inches

# **Special Features:**

T.O.-43-D71-924;

# **NSN 5985-01-262-2554** Waveguide Assembly - Page 2 of 2



Flexibility:
Flexible single tubing segment
Material:
Rubber single tubing jacket
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver all tubing segment and flange outside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0