## NSN 5985-01-262-2952

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-262-2952

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Terminal Material:
Steel, stainless and beryllium copper, qq-c-530
Terminal Surface Treatment:
Gold plated, mil-g-45204
Body Surface Treatment:
Passivated, qq-p-35
Overall Length:
1.220 inches
Overall Diameter:
0.380 inches
Operating Tempurature Range:
+13.0/+28.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
5.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Temperature Sensitivity Attenuation In Decibels:
0.1000
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz

## NSN 5985-01-262-2952

Fixed Attenuator - Page 2 of 2



**Precious Material And Location:** 

Inner contact surfaces gold

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000