

View Online at <https://aerobasegroup.com/nsn/5985-01-262-2955>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

Err-090

**Terminal Material:**

Steel, stainless and beryllium copper, qq-c-530

**Terminal Surface Treatment:**

Gold plated, mil-g-45204

**Body Surface Treatment:**

Passivated, qq-p-35

**Overall Length:**

1.220 inches

**Overall Diameter:**

0.380 inches

**Operating Temperature Range:**

+13.0/+28.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.15 and 1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average

**Rf Signal Attenuation In Decibels:**

8.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Temperature Sensitivity Attenuation In Decibels:**

0.1000

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 12.400 gigahertz

**Precious Material And Location:**

Inner contact surfaces gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000