## NSN 5985-01-262-5897

Fixed Attenuator - Page 1 of 2



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-01-262-5897
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.020 inches
Overall Diameter:
0.312 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.07
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+8.0 gigahertz
Attenuation Accuracy Reference Frequency:
8.0 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 8.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment

## NSN 5985-01-262-5897

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

