NSN 5985-01-262-5901

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-262-5901

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
5.760 inches
Bolt Circle Diameter:
3.500 inches
Overall Height:
2.340 inches
Overall Width:
5.000 inches
First Flat Length:
0.488 inches
Flat Height:
0.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
20.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.700 gigahertz and 1.900 gigahertz
Mounting Thread Quantity:

32 per inch

NSN 5985-01-262-5901

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position circular Shaft Type: Round, flatted Mounting Facility Screw Thread Diameter: 0.138 inches Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: - Demilitarization:

Yes - demil/mli

Fiig: A223a0