## NSN 5985-01-263-5206

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-263-5206

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
6.610 inches
Overall Height:
1.380 inches
Overall Width:
2.500 inches
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.6
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Accuracy Reference Frequency:
3.3 gigahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
4
Attenuation Per Step In Decibels:
1.0 and 2.0 and 4.0 and 8.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 3.100 gigahertz and 3.500 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.25/+0.25
Adjustment Device Type And Quantity:
1 electronic, current controlled and 1 electronic, voltage controlled
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female and 1 connector, receptacle
Shelf Life:
A1/-

N/a

## NSN 5985-01-263-5206

Variable Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A223a0