NSN 5985-01-263-6032

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-263-6032

| Body Style: |
|--|
| Rectangular |
| Overall Length: |
| 1.840 inches |
| Overall Height: |
| 1.840 inches |
| Overall Width: |
| 0.750 inches |
| Frequency Rating: |
| 0.9 gigahertz single frequency operating and 13.0 gigahertz single frequency operating |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| |
| Switch Type: |
| Nontransfer |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 2.00 single |
| Insertion Loss In Decibels: |
| 2.20 single |
| Coaxial Connector Series Designation: |
| Sma |
| Connector End Design: |
| Female |
| Rf Power Handling Capability: |
| 5.0 watts average single |
| Minimum Crosstalk Rating In Decibels: |
| 60.0 single |
| Actuator Operating Method: |
| Solid state |
| Switching Time: |
| 0.1 milliseconds |
| Pole Quantity: |
| 1 |
| Throw Quantity: |
| 2 |
| Rf Maximum Voltage Rating: |
| 15.0 volts peak |
| Coupling Position Quantity: |
| 4 |
| Mounting Facility Type And Quantity: |

3 unthreaded hole

NSN 5985-01-263-6032

Radio Frequency Transmission Line Switch - Page 2 of 2



| Mounting Facility Pattern: |
|--|
| Obtuse triangle single mounting facility pattern |
| Terminal Type And Quantity: |
| 2 turret and 1 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A158a0