

View Online at <https://aerobasegroup.com/nsn/5985-01-264-2213>

**Application Design:**

Transmission line

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Err-090

**Terminal Material:**

Steel, stainless

**Terminal Surface Treatment:**

Passivated

**Body Surface Treatment:**

Passivated

**Overall Length:**

Between 1.200 inches and 1.240 inches

**Overall Diameter:**

Between 0.360 inches and 0.400 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**End Application:**

An/alq-17 (1) i.S.S.

**Voltage Standing Wave Ratio:**

1.15 and 1.30 and 1.35

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average and 0.2 kilowatts peak

**Rf Signal Attenuation In Decibels:**

12.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

**Attenuation Accuracy Reference Frequency:**

18.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.50/+0.60

**Connection Type Per Function:**

Male output and female input

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Specification Data:**

28527-2139904 manufacturers source control

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000