

View Online at <https://aerobasegroup.com/nsn/5985-01-264-2906>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.620 inches all flanges and 0.624 inches all flanges

**Flange Inside Height:**

0.309 inches all flanges and 0.313 inches all flanges

**Flange Outside Width:**

1.297 inches all flanges and 1.327 inches all flanges

**Flange Outside Height:**

1.297 inches all flanges and 1.327 inches all flanges

**Flange Inside Diameter:**

0.985 inches all flanges and 1.015 inches all flanges

**Flange Depth:**

0.360 inches all flanges and 0.390 inches all flanges

**Flange Connecting Hole Diameter:**

0.144 inches all flanges all connection facilities and 0.147 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.15

**Maximum Operating Pressure:**

10.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.699 inches and 0.705 inches

**Waveguide Inside Width:**

0.622 inches

**Waveguide Inside Height:**

0.311 inches

**Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges all connection facilities

**Flange Style:**

Choke type all flanges

**Flexibility:**

Rigid third tubing segment

**Material:**

Copper alloy third tubing segment

**Precious Material And Location:**

Internal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver second tubing segment inside surfaces

**Specification Data:**

53711-5543098 manufacturers source control

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0