NSN 5985-01-264-2910

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-264-2910

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches first flange and 0.624 inches first flange

Flange Inside Height:

0.309 inches first flange and 0.313 inches first flange

Flange Outside Width:

1.297 inches first flange and 1.327 inches first flange

Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Waveguide Longer Offset Distance:

Between 5.475 inches and 5.505 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

NSN 5985-01-264-2910 Waveguide Assembly - Page 2 of 2

Fiig: A073a0



Flange Style:
Choke type first flange
Waveguide Offset Distance:
Between 0.455 inches and 0.485 inches
Special Features:
Includes 1.15 x 0.75 x 0.090 in. Mtg flange w/0.159 in. Diameter mtg hole
Flexibility:
Rigid all tubing segment
Material:
Copper alloy all tubing segment and flange
Surface Treatment:
Primer all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli