## NSN 5985-01-264-5433

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-264-5433

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

0.620 inches second flange and 0.624 inches second flange

#### Flange Inside Height:

0.309 inches second flange and 0.313 inches second flange

#### Flange Outside Width:

1.297 inches second flange and 1.327 inches second flange

## Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

#### Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

## Flange Depth:

0.985 inches second flange and 1.015 inches second flange

#### Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities

## **Voltage Standing Wave Ratio:**

1.07

## Thready Qty Per Inch (tpi):

32 first flange all connection facilities

#### **Maximum Operating Pressure:**

10.0 pounds per square inch gage

## Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

## Thread Size:

0.138 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

## Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

## **Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

#### **Waveguide Longer Offset Distance:**

Between 1.610 inches and 1.640 inches

# NSN 5985-01-264-5433

Waveguide Assembly - Page 2 of 2



## Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

**Waveguide Offset Distance:** 

Between 1.056 inches and 1.085 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

**Surface Treatment:** 

Any acceptable all tubing segment and flange all surfaces

**Style Designator:** 

Bend type

**Thread Series Designator:** 

Unc first flange all connection facilities

**Fsc Application Data:** 

Antennas, waveguides and related equip.

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A073a0