NSN 5985-01-264-7489



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-264-7489 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 7.000 inches **Overall Height:** 1.620 inches **Overall Width:** 3.000 inches **Unthreaded Mounting Hole Diameter:** 0.162 inches **Voltage Standing Wave Ratio:** 1.30 **Coaxial Connector Series Designation:** Sma **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.4 **Overall Attenuation Range In Decibels:** +0.0/+25.5 **Attenuation Variation Method:** Stepped **Step Position Quantity: Attenuation Per Step In Decibels:** 0.75 **Mounting Facility Type And Quantity:** 12 unthreaded hole Frequency Range: Between 520.000 megahertz and 560.000 megahertz **Overall Attenuation Accuracy In Decibels: Adjustment Device Type And Quantity:** 1 electronic, programmable Impedance Rating In Ohms: 50.0 output **Terminal Type And Quantity:** 2 connector, coaxial, female and 11 turret Shelf Life: N/a

. . .

Unit Of Measure:

NSN 5985-01-264-7489

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0