NSN 5985-01-264-7490

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-264-7490

| Application Design: |
|--|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 7.000 inches |
| Overall Height: |
| 1.620 inches |
| Overall Width: |
| 3.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.162 inches |
| Voltage Standing Wave Ratio: |
| 1.30 |
| Coaxial Connector Series Designation: |
| Sma |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.4 |
| Overall Attenuation Range In Decibels: |
| +0.0/+55.5 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 74 |
| Attenuation Per Step In Decibels: |
| 0.75 |
| Mounting Facility Type And Quantity: |
| 12 unthreaded hole |
| Frequency Range: |
| Between 520.000 megahertz and 560.000 megahertz |
| Overall Attenuation Accuracy In Decibels: |
| -0.60/+0.60 |
| Adjustment Device Type And Quantity: |
| 1 electronic, programmable |
| Impedance Rating In Ohms: |
| 50.0 output |
| Terminal Type And Quantity: |
| 2 connector, coaxial, female and 11 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5985-01-264-7490

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0