## NSN 5985-01-267-1345

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-267-1345

Application Design:
Transmission line
Body Material:
Steel
Body Style:
Err-090
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Passivated
Overall Length:
Between 0.830 inches and 0.890 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-40.0/+71.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
7.0
Voltage Standing Wave Ratio Frequency Range:
+13.5/+17.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
5.25 grams
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Detween 12 E00 sizehertz and 17 000 sizehertz

Between 13.500 gigahertz and 17.000 gigahertz

## NSN 5985-01-267-1345

Fixed Attenuator - Page 2 of 2



**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000