# NSN 5985-01-267-1350

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-267-1350

# Application Design: Transmission line Body Material:

Steel

## Body Style:

1b round, terminal/terminals in opposite surface

#### **Terminal Material:**

Steel, stainless

#### **Terminal Surface Treatment:**

Passivated

#### **Body Surface Treatment:**

Passivated

#### Overall Length:

Between 1.000 inches and 1.040 inches

#### **Overall Diameter:**

0.280 inches

#### **Operating Tempurature Range:**

-40.0/+71.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.35

#### Input Impedance Rating In Ohms:

50.0

### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Sma

#### **Rf Signal Attenuation In Decibels:**

14.0

#### Voltage Standing Wave Ratio Frequency Range:

+13.5/+17.0 gigahertz

#### Attenuation Accuracy In Decibels:

-0.50/+0.50

#### **Connection Type Per Function:**

Female input and male output

#### **Unpackaged Unit Weight:**

5.25 grams

#### **Mounting Method:**

Connector

### **Terminal Type And Quantity:**

2 connector

#### **Frequency Range:**

Between 13.500 gigahertz and 17.000 gigahertz

# NSN 5985-01-267-1350

Fixed Attenuator - Page 2 of 2



**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000