NSN 5985-01-267-2787

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-267-2787

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.840 inches
Overall Height:
0.560 inches
Overall Width:
3.000 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
5.0 watts average and 3.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 2.000 gigahertz and 4.000 gigahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
Adjustment Device Type And Quantity: 1 knob w/dial
1 knob w/dial
1 knob w/dial Mounting Facility Pattern:
1 knob w/dial Mounting Facility Pattern: Four position rectangular

2 connector, coaxial, female

NSN 5985-01-267-2787

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0