NSN 5985-01-268-3290

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-268-3290

1	Application Design:
٦	Transmission line
E	Body Style:
(Coaxial type
(Overall Length:
7	7.000 inches
(Overall Height:
1	1.620 inches
(Overall Width:
3	3.000 inches
ι	Unthreaded Mounting Hole Diameter:
(0.160 inches
١	Voltage Standing Wave Ratio:
1	1.30
(Coaxial Connector Series Designation:
S	Sma
I	nsertion Loss At Minimum Attenuation In Maximum Decibels
1	1.0
(Overall Attenuation Range In Decibels:
+	+0.0/+50.0
ļ	Attenuation Variation Method:
Ś	Stepped
ç	Step Position Quantity:
1	10
ļ	Attenuation Per Step In Decibels:
Ę	5.0
	Mounting Facility Type And Quantity:
1	12 unthreaded hole
F	Frequency Range:
E	Between 520.000 megahertz and 560.000 megahertz
(Overall Attenuation Accuracy In Decibels:
-	1.00/+1.00
ļ	Adjustment Device Type And Quantity:
1	1 electronic, programmable
I	mpedance Rating In Ohms:
Ę	50.0 output
٦	Terminal Type And Quantity:
2	2 connector, coaxial, female and 8 turret
Ş	Shelf Life:
r	N/a

NSN 5985-01-268-3290

Variable Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A223a0

