## NSN 5985-01-268-4312

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-268-4312

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.400 inches
Overall Height:
2.360 inches
Overall Width:
3.270 inches
Voltage Standing Wave Ratio:
1.60 and 2.00
Coaxial Connector Series Designation:
Wpm
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.5
Overall Attenuation Range In Decibels:
+0.0/+90.0
Attenuation Accuracy Reference Frequency:
40.0 gigahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
9
Attenuation Per Step In Decibels:
10.0
Frequency Range:
Between 0.000 gigahertz and 40.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.50/+1.50
Segment Attenuation Range In Decibels:
+0.00/+10.00
Adjustment Device Type And Quantity:
1 knob w/dial
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

N/a

## NSN 5985-01-268-4312

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0