# NSN 5985-01-270-7051

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-270-7051

### Application Design:

Transmission line

## **Body Material:**

Steel

# Body Style:

Err-090

#### **Overall Length:**

0.870 inches

#### **Overall Diameter:**

0.317 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.10 and 1.15 and 1.20 and 1.25 and 1.35

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:** 

Sma

#### **Power Rating:**

2.0 watts average

## **Rf Signal Attenuation In Decibels:**

1.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0/+2.0 gigahertz and +2.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

## **Connection Type Per Function:**

Female input and male output

## Unpackaged Unit Weight:

0.450 ounces

## Mounting Method:

Connector

## Terminal Type And Quantity:

2 connector

# Frequency Range:

Between 0.000 gigahertz and 18.000 gigahertz

# Test Data Document:

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-a-3933/25 government specification

# Shelf Life:

N/a

# NSN 5985-01-270-7051

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A20000

