## NSN 5985-01-271-7249

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-271-7249

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange single connection facility

**Thread Direction:** 

Right-hand first flange single connection facility

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches second flange

Flange Inside Height:

0.222 inches second flange

Flange Outside Width:

0.735 inches first flange and 0.765 inches first flange

Flange Outside Height:

0.735 inches first flange and 0.765 inches first flange

Flange Inside Diameter:

0.485 inches first flange and 0.515 inches first flange

Flange Depth:

0.195 inches first flange and 0.225 inches first flange

Flange Connecting Hole Diameter:

0.116 inches second flange single connection facility

**Voltage Standing Wave Ratio:** 

1.08

**Insertion Loss In Decibels:** 

0.20

Thready Qty Per Inch (tpi):

40 first flange single connection facility

**Maximum Operating Pressure:** 

30.0 pounds per square inch gage

**Waveguide Outside Width:** 

Between 0.358 inches and 0.362 inches

**Thread Size:** 

0.112 inches first flange single connection facility

Waveguide Inside Width:

Between 0.279 inches and 0.282 inches

**Waveguide Inside Height:** 

Between 0.139 inches and 0.142 inches

**Waveguide Outside Height:** 

Between 0.218 inches and 0.222 inches

## **NSN 5985-01-271-7249** Waveguide Assembly - Page 2 of 2

Fiig: A073a0



Flange Connecting Facility And Quantity:
4 unthreaded hole second flange single connection facility
Flange Style:
Cover type second flange
Waveguide Length:
Between 0.730 inches and 0.740 inches
Special Features:
Frequency rated at 33; 33.2; 33.4ghz
Flexibility:
Rigid single tubing segment
Material:
Copper alloy single tubing segment and flange
Precious Material And Location:
External surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver single tubing segment and flange outside surfaces and primer single tubing segment and flange outside surfaces and enamel single
tubing segment and flange outside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange single connection facility
Fsc Application Data:
Radar equipment
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No