

View Online at <https://aerobasegroup.com/nsn/5985-01-271-7250>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches second flange

Flange Inside Height:

0.222 inches first flange

Flange Outside Width:

0.745 inches first flange and 0.755 inches first flange

Flange Outside Height:

0.745 inches first flange and 0.755 inches first flange

Flange Depth:

0.182 inches first flange and 0.192 inches first flange

Flange Connecting Hole Diameter:

0.116 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.50

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.358 inches and 0.362 inches

Waveguide Inside Width:

Between 0.279 inches and 0.282 inches

Waveguide Inside Height:

Between 0.139 inches and 0.142 inches

Waveguide Outside Height:

Between 0.218 inches and 0.222 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

Between 1.593 feet and 1.595 feet

Flexibility:

Rigid single tubing segment

Material:

Copper alloy single tubing segment and flange

Precious Material And Location:

Internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver single tubing segment and flange inside surfaces

Style Designator:

Straight type

Fsc Application Data:

Radar equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0