NSN 5985-01-271-9982

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-271-9982

Application Design:
Transmission line
Body Style:
Cylindrical w/side terminals
Overall Length:
3.250 inches
Overall Width:
2.800 inches
Body Diameter:
2.900 inches
Body Length:
2.100 inches
Distance Between Mounting Facility Centers:
1.500 inches
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
6.0
Overall Attenuation Range In Decibels:
+1.0/+40.0
Attenuation Accuracy Reference Frequency:
100.0 kilohertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
24
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded stud
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob w/dial
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:

600.0 input-output

NSN 5985-01-271-9982

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity:
6 pin
Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0