NSN 5985-01-272-3443

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-272-3443

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches second flange and 0.364 inches second flange

Flange Inside Height:

0.222 inches second flange and 0.224 inches second flange

Flange Outside Width:

0.735 inches first flange and 0.765 inches first flange

Flange Outside Height:

0.735 inches first flange and 0.765 inches first flange

Flange Inside Diameter:

0.485 inches first flange and 0.515 inches first flange

Flange Depth:

0.195 inches first flange and 0.225 inches first flange

Flange Connecting Hole Diameter:

0.116 inches second flange all connection facilities and 0.118 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.20

Waveguide Outside Width:

Between 0.358 inches and 0.362 inches

Thread Size:

0.112 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.279 inches and 0.282 inches

Waveguide Inside Height:

Between 0.139 inches and 0.142 inches

Waveguide Outside Height:

Between 0.218 inches and 0.222 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Waveguide First Leg Length:

0.495 inches

NSN 5985-01-272-3443

Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type second flange
Waveguide Second Leg Length:
0.695 inches
Waveguide Third Leg Length:
1.448 inches
Waveguide Fourth Leg Length:
2.440 inches
Flexibility:
Rigid all tubing segment
Material:
Metal all tubing segment and flange
Precious Material And Location:
Flange face surfaces rhodium and flange face surfaces silver
Precious Material:
Rhodium and silver
Surface Treatment:
Enamel all tubing segment and flange outside surfaces
Style Designator:
Three bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0