NSN 5985-01-272-4116

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-272-4116

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.279 inches all flanges and 0.281 inches all flanges

Flange Inside Height:

0.139 inches all flanges and 0.141 inches all flanges

Flange Outside Width:

0.735 inches all flanges and 0.765 inches all flanges

Flange Outside Height:

0.735 inches all flanges and 0.765 inches all flanges

Flange Depth:

0.195 inches all flanges and 0.225 inches all flanges

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.20

Waveguide Outside Width:

0.360 inches

Thread Size:

0.112 inches all flanges all connection facilities

Waveguide Inside Width:

0.280 inches

Waveguide Inside Height:

0.140 inches

Waveguide Outside Height:

0.220 inches

Waveguide Longer Offset Distance:

1.300 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Offset Distance:

0.804 inches

NSN 5985-01-272-4116 Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid all tubing segment
Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
External surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver all tubing segment inside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0