NSN 5985-01-273-3964

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-3964

Application Design:
Transmission line
Body Material:
Aluminum alloy
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Surface Treatment:
Gold plated, mil-g-45204
Overall Length:
0.650 inches
Overall Height:
0.040 inches
Overall Width:
0.375 inches
Operating Tempurature Range:
-55.0/+150.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.35 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
1.5 watts average
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Printed circuit
Terminal Type And Quantity:
3 ribbon
Frequency Range:
Between 0.000 hertz and 12.000 gigahertz
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Shelf Life:

N/a

NSN 5985-01-273-3964

Fixed Attenuator - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000