NSN 5985-01-273-3965

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-3965 **Application Design:** Transmission line **Body Material:** Aluminum alloy **Body Style:** Rectangular terminal/terminals on three surfaces **Terminal Surface Treatment:** Gold plated, mil-g-45204 **Overall Length:** 0.650 inches **Overall Height:** 0.040 inches **Overall Width:** 0.375 inches **Operating Tempurature Range:** -55.0/+150.0 degrees celsius **Voltage Standing Wave Ratio:** 1.25 and 1.35 and 1.50 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 1.5 watts average **Rf Signal Attenuation In Decibels:** 7.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Mounting Method:** Printed circuit **Terminal Type And Quantity:** 3 ribbon Frequency Range: Between 0.000 hertz and 12.000 gigahertz **Precious Material And Location:** Terminals gold **Precious Material:** Gold

N/a

Shelf Life:

NSN 5985-01-273-3965

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000