## NSN 5985-01-273-3966

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-3966

Analisation Design.
Application Design:
Body Material:
Aluminum alloy
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Surface Treatment:
Gold plated, mil-g-45204
Overall Length:
0.650 inches
Overall Height:
0.040 inches
Overall Width:
0.375 inches
Operating Tempurature Range:
-55.0/+150.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.35 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
1.5 watts average
Rf Signal Attenuation In Decibels:
8.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Printed circuit
Terminal Type And Quantity:
3 ribbon
Frequency Range:
Between 0.000 hertz and 12.000 gigahertz
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Shelf Life:
N/a

## NSN 5985-01-273-3966

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000

