NSN 5985-01-273-3968

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-273-3968

Transmission line
Body Material:
Aluminum alloy
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Surface Treatment:
Gold plated, mil-g-45204
Overall Length:
0.650 inches
Overall Height:
0.040 inches
Overall Width:
0.375 inches
Operating Tempurature Range:
-55.0/+150.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
1.5 watts average
Rf Signal Attenuation In Decibels:
12.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy In Decibels:
Attenuation Accuracy In Decibels: -0.75/+0.50
•
-0.75/+0.50
-0.75/+0.50 Mounting Method:
-0.75/+0.50 Mounting Method: Printed circuit
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity:
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity: 3 ribbon
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity: 3 ribbon Frequency Range:
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity: 3 ribbon Frequency Range: Between 0.000 hertz and 4.000 gigahertz
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity: 3 ribbon Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location:
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity: 3 ribbon Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Terminals gold
-0.75/+0.50 Mounting Method: Printed circuit Terminal Type And Quantity: 3 ribbon Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Terminals gold Precious Material:

NSN 5985-01-273-3968

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000