# NSN 5985-01-273-3969

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-3969

# Application Design:

Transmission line

#### **Body Material:**

Any acceptable

# Body Style:

Rectangular terminal/terminals on three surfaces

# **Body Surface Treatment:**

Any acceptable

#### **Overall Length:**

0.647 inches

#### **Overall Height:**

0.040 inches

#### **Overall Width:**

0.372 inches

#### Voltage Standing Wave Ratio:

## 1.25 and 1.35 and 1.50

# Input Impedance Rating In Ohms:

50.0

# **Output Impedance Rating In Ohms:**

50.0

# **Power Rating:**

1.5 watts average

# **Rf Signal Attenuation In Decibels:**

1.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz

## **Attenuation Accuracy Reference Frequency:**

12.0 gigahertz

## Attenuation Accuracy In Decibels:

-0.50/+0.50

## Mounting Method:

Terminal

## **Terminal Type And Quantity:**

3 ribbon

# Frequency Range:

Between 0.000 hertz and 12.000 gigahertz

# Fsc Application Data:

Antennas, waveguides, and related equipment

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5985-01-273-3969

Fixed Attenuator - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A20000

