NSN 5985-01-273-8021

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-273-8021

Application Design:				
Transmission line				
Body Material:				
Metal				
Body Style:				
Rectangular, terminal/terminals on opposite surfaces				
Overall Length:				
0.870 inches				
Overall Height:				
0.317 inches				
Overall Width:				
0.317 inches				
Operating Tempurature Range:				
-55.0/+125.0 degrees celsius				
Voltage Standing Wave Ratio:				
1.15				
Input Impedance Rating In Ohms:				
50.0				
Output Impedance Rating In Ohms:				
50.0				
Coaxial Connector Series Designation:				
Sma				
Power Rating:				
2.0 watts average and 500.0 watts peak				
Rf Signal Attenuation In Decibels:				
4.0				
Voltage Standing Wave Ratio Frequency Range:				
+0.0/+18.0 gigahertz				
Attenuation Accuracy In Decibels:				
-0.30/+0.30				
Connection Type Per Function:				
Female input and male output				
Unpackaged Unit Weight:				
0.450 ounces				
Mounting Method:				
Connector				
Terminal Type And Quantity:				
2 connector				
Frequency Range:				
Between 0.000 hertz and 18.000 gigahertz				
Test Data Document:				
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).				

NSN 5985-01-273-8021

Fixed Attenuator - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-a-3933/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000