NSN 5985-01-273-9817

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-01-273-9817

Application Design:

Transmission line

Body Material:

Metal

Body Style:

Rectangular terminal/terminals on three surfaces

Body Surface Treatment:

Any acceptable

Overall Length:

0.147 inches

Overall Height:

0.030 inches

Overall Width:

0.122 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Power Rating:

0.5 watts average

Rf Signal Attenuation In Decibels:

4.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz

Attenuation Accuracy Reference Frequency:

4.0 gigahertz

Attenuation Accuracy In Decibels:

-0.20/+0.20

Terminal Type And Quantity:

3 tab, solder lug

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Contacts gold and contacts platinum

Precious Material:

Gold and platinum

Fsc Application Data:

Antennas, waveguides, and related equipment



NSN 5985-01-273-9817

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

